



SGL-A

Thread	D	h	g	t	d	n - m	MAX. Nm
SGL-A M14 x 1.5	30	14	4	2	25	2 - M4	3.5
SGL-A M15 x 1	30	14	4	2	25	2 - M4	3.5
SGL-A M16 x 1.5	30	14	4	2	25	2 - M4	3.5
SGL-A M17 x 1	32	16	4	2	27	2 - M4	3.5
SGL-A M18 x 1.5	32	16	4	2	27	3 - M4	3.5
SGL-A M20 x 1	38	16	4	2	33	3 - M4	3.5
SGL-A M20 x 1.5	38	16	4	2	33	3 - M4	3.5
SGL-A M22 x 1.5	38	16	4	2	33	3 - M4	3.5
SGL-A M24 x 1.5	38	18	5	2	33	3 - M4	3.5
SGL-A M25 x 1.5	38	18	5	2	33	3 - M4	3.5
SGL-A M27 x 1.5	40	18	5	2	35	3 - M4	3.5
SGL-A M30 x 1.5	45	18	5	2	40	3 - M4	3.5
SGL-A M33 x 1.5	50	18	5	2	45	3 - M4	3.5
SGL-A M35 x 1.5	52	18	5	2	47	3 - M6	8.0
SGL-A M36 x 1.5	52	18	5	2	47	3 - M6	8.0
SGL-A M39 x 1.5	58	20	6	2.5	52	3 - M6	8.0
SGL-A M40 x 1.5	58	20	6	2.5	52	3 - M6	8.0
SGL-A M42 x 1.5	62	20	6	2.5	56	3 - M6	8.0
SGL-A M45 x 1.5	65	20	6	2.5	59	3 - M6	8.0
SGL-A M48 x 1.5	70	20	6	2.5	64	3 - M6	8.0
SGL-A M50 x 1.5	70	20	6	2.5	64	3 - M6	8.0
SGL-A M52 x 1.5	73	22	7	3	68	3 - M6	8.0
SGL-A M55 x 2	75	22	7	3	68	3 - M6	8.0
SGL-A M56 x 2	75	22	7	3	68	3 - M6	8.0
SGL-A M60 x 2	80	22	7	3	73	3 - M6	8.0
SGL-A M64 x 2	85	22	7	3	78	3 - M6	8.0
SGL-A M65 x 2	85	22	7	3	78	3 - M6	8.0

SGL-A 軸向鎖定

此型螺帽鎖定方式為軸向三點式鎖定，其厚度與SGL-F系列相同，軸向三點式鎖定為其特點，適用於裝配工作的特殊環境限制。

螺帽本身之內螺紋、端面、背面、外圓都經過精密研磨加工，可符合高速旋轉所要求的精度。

- 材質：SCM440(42CrMo4)調質
- 螺紋精度：ISO 4H精密研磨
- 平面偏擺：0.002mm
- 硬度：HRC 28° ~ 32°
- 平行度：0.002mm
- 同心度：0.005mm



Thread	D	h	g	t	d	n - m	MAX. Nm
SGL-A M68 x 2	92	24	8	3.5	84	3 - M8	18.0
SGL-A M70 x 2	92	24	8	3.5	84	3 - M8	18.0
SGL-A M72 x 2	94	24	8	3.5	86	3 - M8	18.0
SGL-A M75 x 2	98	24	8	3.5	90	3 - M8	18.0
SGL-A M76 x 2	98	24	8	3.5	90	3 - M8	18.0
SGL-A M80 x 2	105	24	8	3.5	96	3 - M8	18.0
SGL-A M85 x 2	110	24	8	3.5	102	3 - M8	18.0
SGL-A M90 x 2	120	26	10	4	108	3 - M8	18.0
SGL-A M95 x 2	125	26	10	4	113	3 - M8	18.0
SGL-A M100 x 2	130	26	10	4	118	3 - M8	18.0
SGL-A M105 x 2	140	28	12	5	125	3 - M8	18.0
SGL-A M110 x 2	145	28	12	5	132	3 - M8	18.0
SGL-A M115 x 2	150	28	12	5	137	3 - M8	18.0
SGL-A M120 x 2	155	30	12	5	142	3 - M8	18.0
SGL-A M125 x 2	160	30	12	5	147	3 - M8	18.0
SGL-A M130 x 2	165	30	12	5	152	3 - M8	18.0
SGL-A M135 x 2	175	32	14	6	160	3 - M10	35.0
SGL-A M140 x 2	180	32	14	6	165	3 - M10	35.0
SGL-A M145 x 2	190	32	14	6	175	3 - M10	35.0
SGL-A M150 x 2	195	32	14	6	180	3 - M10	35.0
SGL-A M155 x 3	200	34	16	7	180	3 - M10	35.0
SGL-A M160 x 3	210	34	16	7	190	3 - M10	35.0
SGL-A M165 x 3	210	34	16	7	190	3 - M10	35.0
SGL-A M170 x 3	220	34	16	7	200	3 - M10	35.0
SGL-A M180 x 3	230	36	18	8	205	3 - M12	60.0
SGL-A M190 x 3	240	36	18	8	215	3 - M12	60.0
SGL-A M200 x 3	250	38	18	8	225	3 - M12	60.0