



此型螺帽較SBL-A螺帽不同在於螺帽本身背面增加了可調整的平衡螺絲孔，可解決高速主軸在調校平衡的不方便和精度。
本設計再配合公司所開發的消音螺絲將其平衡螺絲孔塞住，可完全降低高速所帶來的噪音問題。

- 材質:SCM440(42CrMo4)調質
- 螺紋精度:ISO 4H精密研磨
- 平面偏擺:0.002mm
- 硬度:HRC48° ~ 52°
- 平行度:0.002mm
- 同心度:0.005mm

SBL-B

Thread	D	h	d	U x V	C	F	m x n	MAX.Nm	Loosening Torque Nm
SBL-B M20 x 1	38	16	33	M4 x 6	13	10	M5 x 3	4.5	28.9
SBL-B M20 x 1.5					16		M6 x 3		
SBL-B M25 x 1.5					19		M5 x 9		
SBL-B M30 x 1.5	45	18	40	M5 x 9	22	12	M8 x 3	8.0	32.4
SBL-B M35 x 1.5	25								
SBL-B M40 x 1.5	28								
SBL-B M45 x 1.5	52	20	47	M6 x 9	30	14	M8 x 3	18.0	39.2
SBL-B M50 x 1.5	33								
SBL-B M55 x 2	35								
SBL-B M60 x 2	70	22	52	M6 x 12	35	16	M8 x 6	18.0	46.1
SBL-B M65 x 2	38								
SBL-B M70 x 2	41								
SBL-B M75 x 2	80	24	59	M6 x 12	43	18	M8 x 6	18.0	61.8
SBL-B M80 x 2	46								
SBL-B M85 x 2	49								
SBL-B M90 x 2	92	26	64	M8 x 12	53	20	M10 x 6	35.0	176.5
SBL-B M95 x 2	55								
SBL-B M100 x 2	58								
SBL-B M105 x 2	98	28	70	M8 x 12	61	22	M10 x 6	35.0	201.0
SBL-B M110 x 2	64								
SBL-B M115 x 2	66								
SBL-B M120 x 2	105	30	73	M8 x 12	69	24	M10 x 6	35.0	220.6
SBL-B M125 x 2	71								
SBL-B M130 x 2	74								
SBL-B M135 x 2	110	32	78	M8 x 12	78	26	M10 x 6	35.0	236.3
SBL-B M140 x 2	80								
SBL-B M145 x 2	84								
SBL-B M150 x 2	120	32	84	M8 x 12	86	26	M10 x 6	35.0	252.0
SBL-B M155 x 2	86								
SBL-B M160 x 2	88								