



此型螺帽不同於SBL-D型螺帽在於其平衡螺絲孔位於螺帽外圍，當平衡調整無法從背面調整時，此型為最佳的代替品，配合消音螺絲，可降低高速所帶來的噪音問題。

- 材質:SCM440(42CrMo4)調質
- 螺紋精度:ISO 4H精密研磨
- 平面偏擺:0.002mm
- 硬度:HRC48° ~ 52°
- 平行度:0.002mm
- 同心度:0.005mm



SBL-E

Thread	D	h	d	U x V	C	F	m x n	MAX.Nm	Loosening Torque Nm
SBL-E M20 x 1	32	10	27	M5 x 6	5	3	M5 x 3	4.5	24.0
SBL-E M20 x 1.5									
SBL-E M25 x 1.5	38	12	33	M5 x 9	6	4	M6 x 3	8.0	26.5
SBL-E M30 x 1.5									
SBL-E M35 x 1.5	45	14	40	M6 x 9	7	5	M6 x 3	8.0	28.4
SBL-E M40 x 1.5									
SBL-E M45 x 1.5	52	16	47	M6 x 12	8	6	M6 x 3	8.0	34.3
SBL-E M50 x 1.5									
SBL-E M55 x 2	58	18	52	M8 x 6	9	8	M8 x 6	18.0	36.3
SBL-E M60 x 2									
SBL-E M65 x 2	65	20	59	M8 x 12	10	9	M8 x 6	18.0	56.9
SBL-E M70 x 2									
SBL-E M75 x 2	70	22	64	M10 x 6	11	11	M10 x 6	35.0	63.7
SBL-E M80 x 2									
SBL-E M85 x 2	75	24	68	M10 x 6	12	14	M10 x 6	35.0	68.6
SBL-E M90 x 2									
SBL-E M95 x 2	80	26	73	M10 x 6	13	16	M10 x 6	35.0	96.1
SBL-E M100 x 2									
SBL-E M105 x 2	85	26	78	M10 x 6	13	16	M10 x 6	35.0	112.7
SBL-E M110 x 2									
SBL-E M115 x 2	92	26	84	M10 x 6	13	16	M10 x 6	35.0	137.3
SBL-E M120 x 2									
SBL-E M125 x 2	98	26	90	M10 x 6	13	16	M10 x 6	35.0	145.1
SBL-E M130 x 2									
SBL-E M135 x 2	105	26	96	M10 x 6	13	16	M10 x 6	35.0	149.0
SBL-E M140 x 2									
SBL-E M145 x 2	110	26	102	M10 x 6	13	16	M10 x 6	35.0	168.6
SBL-E M150 x 2									
SBL-E M150 x 2	120	20	108	M8 x 12	10	9	M8 x 6	18.0	178.4
SBL-E M150 x 2	125	20	113	M8 x 12	10	9	M8 x 6	18.0	193.1
SBL-E M150 x 2	130	20	118	M8 x 12	10	9	M8 x 6	18.0	210.8
SBL-E M150 x 2	140	20	125	M8 x 12	10	9	M8 x 6	18.0	215.7
SBL-E M150 x 2	145	22	132	M8 x 12	11	11	M8 x 6	18.0	230.4
SBL-E M150 x 2	150	22	137	M8 x 12	11	11	M8 x 6	18.0	250.0
SBL-E M150 x 2	155	22	142	M8 x 12	11	11	M8 x 6	18.0	264.7
SBL-E M150 x 2	160	24	147	M8 x 12	12	14	M8 x 6	18.0	274.5
SBL-E M150 x 2	165	24	152	M8 x 12	12	14	M8 x 6	18.0	294.1
SBL-E M150 x 2	175	24	160	M8 x 12	12	14	M8 x 6	18.0	328.4
SBL-E M150 x 2	180	26	165	M10 x 6	13	16	M10 x 6	35.0	372.5
SBL-E M150 x 2	190	26	175	M10 x 6	13	16	M10 x 6	35.0	402.0
SBL-E M150 x 2	195	26	180	M10 x 6	13	16	M10 x 6	35.0	421.6