



YSFTA此型螺帽之鎖定方式和YSFT一樣，差別在於其外徑和背面設計有扳手孔，方便不同空間組裝之需求。

- 材質: SCM440(42CrMo4)調質
- 硬度: HRC28°~32°
- 螺紋精度: ISO 4H
- 加工方式: 精密研磨
- 平面偏擺: 0.002mm
- 螺紋精度: ISO 4H
- 加工方式: 精密車削
- 平面偏擺: 0.005mm



## YSFTA

Thread	D	h	d	d1	c	c1	n-Øb	n-Øb1	n-m	MAX. Nm
YSFTA-M25 x 1.5P	42	20	35	26	32.5	11	6-Ø4.3	6-Ø4	3-M6	8
YSFTA-M30 x 1.5P	48	20	40	32	40.5	11	6-Ø4.3	6-Ø5	3-M6	8
YSFTA-M35 x 1.5P	53	20	47	38	45.5	11	6-Ø4.3	6-Ø5	3-M6	8
YSFTA-M40 x 1.5P	58	22	52	42	50.5	12	6-Ø4.3	6-Ø5	3-M6	8
YSFTA-M45 x 1.5P	68	22	58	48	58	12	6-Ø4.3	6-Ø6	3-M6	8
YSFTA-M50 x 1.5P	70	24	63	52	61.5	13	6-Ø4.3	6-Ø6	3-M6	8
YSFTA-M55 x 1.5P	75	24	70	58	66.5	13	6-Ø4.3	6-Ø6	3-M6	8
YSFTA-M60 x 1.5P	84	24	75	62	74.5	13	6-Ø5.3	6-Ø6	3-M8	18
YSFTA-M65 x 1.5P	88	25	80	68	78.5	13	6-Ø5.3	6-Ø6	3-M8	18
YSFTA-M70 x 1.5P	95	26	86	72	85	14	6-Ø5.3	6-Ø8	3-M8	18
YSFTA-M75 x 1.5P	100	26	91	77	88	13	6-Ø6.4	6-Ø8	3-M8	18
YSFTA-M80 x 2.0P	110	30	97	83	95	16	6-Ø6.4	6-Ø8	3-M8	18
YSFTA-M85 x 2.0P	115	32	102	88	100	17	6-Ø6.4	6-Ø8	3-M10	35
YSFTA-M90 x 2.0P	120	32	110	93	108	17	6-Ø6.4	6-Ø8	3-M10	35
YSFTA-M95 x 2.0P	125	32	114	98	113	17	6-Ø6.4	6-Ø8	3-M10	35
YSFTA-M100 x 2.0P	130	32	120	103	118	17	6-Ø6.4	6-Ø8	3-M10	35
YSFTA-M110 x 2.0P	140	32	132	112	128	17	6-Ø6.4	6-Ø8	3-M10	35
YSFTA-M120 x 2.0P	155	32	142	122	140	17	6-Ø6.4	6-Ø8	3-M10	35
YSFTA-M130 x 3.0P	165	32	156	132	153	17	6-Ø6.4	6-Ø8	3-M10	35
YSFTA-M140 x 3.0P	180	32	166	142	165	17	6-Ø6.4	6-Ø10	3-M10	35
YSFTA-M150 x 3.0P	190	32	180	152	175	17	6-Ø6.4	6-Ø10	3-M10	35
YSFTA-M160 x 3.0P	205	32	190	162	185	17	6-Ø8.4	6-Ø10	3-M10	35
YSFTA-M170 x 3.0P	215	32	205	172	195	17	6-Ø8.4	6-Ø10	3-M10	35
YSFTA-M180 x 3.0P	230	32	215	182	210	17	6-Ø8.4	6-Ø10	3-M10	35
YSFTA-M190 x 3.0P	240	32	225	192	224	17	6-Ø8.4	6-Ø10	3-M10	35
YSFTA-M200 x 3.0P	245	32	237	202	229	17	6-Ø8.4	6-Ø10	3-M10	35