



※此型螺帽包含螺絲

YSMSW螺帽鎖定方式為利用鋼材本身的彈性，以軸向鎖固，強制鎖定。

本產品因外徑和厚度較大，可承受較大之軸向力。

- 材質: SCM440(42CrMo4)調質
- 硬度: HRC28°~32°
- 螺紋精度: ISO 4H
- 加工方式: 精密車削
- 平面偏擺: 0.005mm



YSMSW

Thread	D	h	h1	g	t	d	n-m	MAX. Nm
YSMSW 20/28-M20 x 1.5P	42	28	11	6	2.5	38	4-M4	3.5
YSMSW 20/40-M20 x 1.5P	52	40	11	7	3	42	4-M4	3.5
YSMSW 25/28-M25 x 1.5P	47	28	11	7	3	43	4-M4	3.5
YSMSW 25/40-M25 x 1.5P	62	40	11	8	3.5	47	4-M4	3.5
YSMSW 30/28-M30 x 1.5P	52	28	11	7	3	48	4-M4	3.5
YSMSW 30/44-M30 x 1.5P	68	44	11	8	3.5	52	4-M4	3.5
YSMSW 35/28-M35 x 1.5P	60	28	11	8	3.5	53	4-M4	3.5
YSMSW 35/44-M35 x 1.5P	73	44	11	8	3.5	60	4-M4	3.5
YSMSW 40/28-M40 x 1.5P	65	28	11	8	3.5	58	6-M4	3.5
YSMSW 40/44-M40 x 1.5P	75	44	11	8	3.5	62	6-M4	3.5
YSMSW 45/28-M45 x 1.5P	70	28	11	8	3.5	63	6-M4	3.5
YSMSW 45/44-M45 x 1.5P	90	44	11	10	4	70	6-M4	3.5
YSMSW 50/32-M50 x 1.5P	75	32	11	8	3.5	68	6-M4	3.5
YSMSW 50/46-M50 x 1.5P	95	46	11	10	4	75	6-M4	3.5
YSMSW 55/46-M55 x 1.5P	100	46	12	10	4	80	6-M5	4.5
YSMSW 60/46-M60 x 1.5P	100	46	12	10	4	85	6-M5	4.5
YSMSW 65/46-M65 x 1.5P	110	46	12	10	4	90	6-M5	4.5
YSMSW 70/46-M70 x 1.5P	115	46	12	10	4	95	6-M5	4.5